



TOOLING INFORMATION REQUEST FORM

To help us best serve you, please complete as many fields as possible and return the form below to: info@Calnanocorp.com

Organization Name	
Contact Name / Email	
Billing Contact Name / Email	
Payment Method	<input type="checkbox"/> Terms <input type="checkbox"/> Credit Card
Billing Address	
Shipping Address	
Desired Delivery Date	
How Did You Hear About Us?	

Tooling Material Desired

- High Strength Graphite (Standard)
- Ultra-High Strength Graphite
- Tungsten Carbide
- Other


Interested in other SPS products or services?

- Sintering or Bonding Service
- Consumables (Graphite Foil, Wool, Twine, etc.)
- SPS Equipment
- Other


DIES: Please provide all dimensions accounting for your foil thickness tolerance.

1) Quantity OD: mm ID: mm L: mm Drawing Provided Y N

2) Quantity OD: mm ID: mm L: mm Drawing Provided Y N



OD (Outside Diameter) & ID (Inside Diameter)



L (Length) & TC (Thermocouple)

Standard depth of the TC hole is usually 3mm from the ID of the die [if the OD is two inches and under]. If the OD is over two inches, then the TC hole will range from 3mm up to 20mm depending on wall thickness. If you would not like a TC hole or you would like a custom TC hole, then please provide your measurements here:

mm

No TC Hole


PUNCHES & SPACERS: Please provide all dimensions accounting for your foil thickness tolerance.

1) Quantity OD: mm L: mm Drawing Provided Y N

2) Quantity OD: mm L: mm Drawing Provided Y N



OD (Outside Diameter)



L (Length)

Special requests (Example: TC):

OTHER/CUSTOM:

Quantity Dimensions (mm) and notes:

Drawing Provided Y N